



HYBRID RECORDER

SBR-EW100/180 Series

HYBRID RECORDER



RKC® RKC INSTRUMENT INC.



EW180 24 dot model



EW100 4 pen model

HYBRID RECORDER SBR-EW100/180 Series

Easy to Use

- Large, VFD full dot matrix display NEW
- Easily navigable interactive settings NEW
- Enables historical trend review during recording NEW
- Internal illumination (high intensity white LED) NEW

Multiple Functions Meet Variety of Needs

- Broad lineup (1,2,3,or 4 pen models, and 6,12,18,24 dot models)
*12,18,24 dot models are only for SBR-EW180
- 6-points dot model achieves one second measurement intervals. NEW
- Universal input
- A wide range of input sensors NEW
- Supports thirty-five types including PLII, PR40-20, and NiNiMo
*Including options
- Mathematical functions
No. of channels: Pen models 8ch
Dot models Max.12ch(EW100) Max.24ch(EW180)
- Computation types: Offers general, logic, relational, and statistical computations.
- Assign/analog record computed results to any channel.
- RS-422A/485 interfaces


Compatible to Previous Model

- The felt-pen, plotter pen, cassette ribbon and chart paper are compatible to previous models (SBR-EY series).
- Rear terminal plate and depth size is same to previous models (SBR-EY series).

More easy to use and easy to read.

Multi-Display (Displays a Variety of Screens) for On-Site Monitoring.

80 kinds of display patterns are prepared.



Navigational display Makes Setup a Snap.

The instrument features a simple configuration, with Operation mode for normal use, and Setting mode for use during setup. In Operation mode, measured values, time, and alarms are updated, and lists are printed. In Setting mode, you can enter measuring ranges, alarm values, and other parameters. Also, Setting mode offers a navigational display that eases entry of settings.



Bright Internal Illumination

By using a high intensity white LED and light diffusing rod for the internal illumination, the visibility of the chart section has been greatly increased.



Chart Ejection Function(EW100)

The chart cassette is equipped with a chart ejection function. You can write memos on the chart and check the historical trend during recording.



Extraction of recorded chart paper is possible


High Reliability and High Quality

Highly Precise & High Reliability of Actuators


The pen servo takes advantage of an ultra-small, rack-and-pinion stepping motor. By eliminating the drive belt, transfer-related loss load is reduced, allowing a smaller servo.

The motor is controlled digitally, yielding reductions in power consumption.


Also, the position of the pen is detected by an optical encoder.



Servo Unit and Optical Encoder



The EW100 series chart cassette can be taken out, without pulling out the operation key board.




Light Weight & Low Power Consumption

High integrated circuit and the new servo unit achieve high efficiencies and low heat emissions in all of the 1-, 2-, 3-, and 4-pen and 6-dot models while simultaneously limiting the weight to approximately 2.5 kg (EW100 6-dot model), and approximately 2.4 kg (EW100 4-pen model).

Long Life & High Speed Scanning

For scanners that switch the input signal, high withstand voltage, low leakage current MOS FETs and high voltage output photocouplers have been combined into a high withstand voltage semiconductor relay offering high speed (6 points per second). At the time of the fastest of 6-dot models) scanning, longer scanner life, and noiseless operation. High integrated circuit achieve reducing power consumption, suppressing heat emissions, and increasing the lifespan of components.



Input signal switch circuit

Compatible to previous model (SBR-EY Series)

1

The felt-pen, plotter pen, cassette ribbon and chart paper are compatible to previous models

A small logo in the bottom right corner, consisting of a blue square on top of a green square.

Rear terminal plate and depth size is same to previous models

EW100 6-dot model



EW180 24-dot model




*Individual terminals are removable, making wiring and maintenance easy.


Ext

External Dimension (Unit:mm)



SBR-EW100



SBR-EW180



Note : Should be mounted by only two brackets, either on the top and bottom



Specifications

Input

Number of inputs : 1,2,3,4 (pen), 6,12*,18*,24* (dot) points
*Only EW180 Series

Input signal

Universal input
TC : R, S, B, K, E, J, T, N, W5Re/W26Re, W3Re/W25Re, L, U
RTD : Pt100, JPt100
DCA : DC current (Using external shunt resistor)
DCV : DC voltage 20/60/200mV, 2/6/20/50V, 1 to 5V
DI : Digital input (Contact or DC Voltage, TTL level)

Measurement range/accuracy: Refer to following table

Recording accuracy

Measurement accuracy \pm (0.3% of recording span)
*Recording span: SBR-EW100: 100mm
SBR-EW180: 180mm

Reference Junction Compensation (when measuring 0°C or up)
TYPE R, S, B, W5Re/W26Re, W3Re/W25Re : $\pm 1^\circ\text{C}$
TYPE K, J, E, T, N, L, U : $\pm 0.5^\circ\text{C}$

Measurement interval

Pen model : 0.125sec/channel
Dot model : 1sec/6dot or 2.5sec/12 to 24dot

Input Resistance:

10M or more (TC, 20mV, 60mV, 200mV range)
Approx. 1M Ω (2V range or more)

Burnout

Available on TC and DCV (1 to 5V) range
•ON/OFF selectable (per channel)
Time constant (2,5,10sec)

Dot model: Moving average
•ON/OFF selectable (per channel)
Moving average cycle (2 to 16)

Computation

Differential computation, Linear scaling
square root, Bias addition

Measurement range/accuracy

Input	Range	Span	Measurement Accuracy	Max. Resolution
DC V	20mV	-20.00 to +20.00mV	$\pm(0.1\% \text{ of reading} + 2\text{digits})$	10 μV
	60mV	-6.00 to +6.00mV		10 μV
	200mV	-200.0 to +200.0mV		100 μV
	2V	-2.00 to +2.00V		1mV
	6V	-6.00 to +6.00V		1mV
	20V	-20.00 to +20.00V		10mV
	50V	-50.00 to +50.00V		10mV
TC	1~5V	1.000 to 5.000V	$\pm(0.1\% \text{ of reading} + 2\text{digits})$	1mV
	R	0.0 to 1760.0°C	$\pm(0.15\% \text{ of reading} + 1^\circ\text{C})$	0.1°C
	S	0.0 to 1760.0°C	but R, S : 0 to 100°C, $\pm 3.7^\circ\text{C}$	
	B	0.0 to 1820.0°C	100 to 300°C, $\pm 1.5^\circ\text{C}$ B : 400 to 600°C, $\pm 2^\circ\text{C}$ and is not guaranteed below 400°C	
	K	-200.0 to +1370.0°C	$\pm(0.15\% \text{ of reading} + 0.7^\circ\text{C})$ but -200 to -100°C: $\pm(0.15\% \text{ of reading} + 1^\circ\text{C})$	
	E	-200.0 to +800.0°C	$\pm(0.15\% \text{ of reading} + 0.5^\circ\text{C})$	
	J	-200.0 to +1100.0°C	$\pm(0.15\% \text{ of reading} + 0.5^\circ\text{C})$	
	T	-200.0 to +400.0°C	but J : -200 to -100°C: $\pm(0.15\% \text{ of reading} + 0.7^\circ\text{C})$	
	N	0.0 to 1300.0°C	$\pm(0.15\% \text{ of reading} + 0.7^\circ\text{C})$	
	W (W5Re/W26Re)	0.0 to 2315.0°C	$\pm(0.15\% \text{ of reading} + 1^\circ\text{C})$	
	L	-200.0 to +900.0°C	$\pm(0.15\% \text{ of reading} + 0.5^\circ\text{C})$	
	U	-200.0 to +400.0°C	but L : -200 to -100°C: $\pm(0.15\% \text{ of reading} + 0.7^\circ\text{C})$	
	WRe (W3Re/W25Re)	0.0 to 2400.0°C	$\pm(0.2\% \text{ of reading} + 1.0^\circ\text{C})$	
-excluding the accuracy of reference junction compensation	PR40-20*1	0.0 to 1900.0°C 0 to 450°C 450 to 750°C 750 to 1100°C 1100 to 1900°C	Not guaranteed $\pm(0.9\% \text{ of reading} + 3.2^\circ\text{C})$ $\pm(0.9\% \text{ of reading} + 1.3^\circ\text{C})$ $\pm(0.9\% \text{ of reading} + 0.4^\circ\text{C})$	
	PLII	0.0 to 1400.0°C	$\pm(0.25\% \text{ of reading} + 2.3^\circ\text{C})$	
	NINMo	0.0 to 1310.0°C	$\pm(0.25\% \text{ of reading} + 0.7^\circ\text{C})$	
	Type N(AWG14)	0.0 to 1300.0°C	$\pm(0.2\% \text{ of reading} + 1.3^\circ\text{C})$	
	W/WRe26	0.0 to 2400.0°C 0 to 400°C 400 to 2400°C	with in $\pm 15.0^\circ\text{C}$ $\pm(0.2\% \text{ of reading} + 2.0^\circ\text{C})$	
	Kp vs Au7Fe	0.0 to 300.0K 0 to 20K 20 to 300K	$\pm 4.5\text{K}$ $\pm 2.5\text{K}$	0.1K
	Pt25	-200.0 to +550.0°C	$\pm(0.15\% \text{ of reading} + 0.6^\circ\text{C})$	
	Pt50	-200.0 to +600.0°C	$\pm(0.3\% \text{ of reading} + 0.6^\circ\text{C})$	
	Ni100(SAMA)	-200.0 to +250.0°C	$\pm(0.15\% \text{ of reading} + 0.4^\circ\text{C})$	
	Ni100(DIN)	-60.0 to +180.0°C	$\pm(0.15\% \text{ of reading} + 0.4^\circ\text{C})$	
RTD	Ni120	-70.0 to +200.0°C	$\pm(0.15\% \text{ of reading} + 0.4^\circ\text{C})$	
	J263*B	0.0 to 300.0K 0 to 40K 40 to 300K	$\pm 3.0\text{K}$ $\pm 1.0\text{K}$	0.1K
	Cu53	-50.0 to +150.0°C	$\pm(0.15\% \text{ of reading} + 0.8^\circ\text{C})$	
	Cu100	-50.0 to +150.0°C	$\pm(0.2\% \text{ of reading} + 1.0^\circ\text{C})$	
	Pt100	-200.0 to +600.0°C	$\pm(0.15\% \text{ of reading} + 0.3^\circ\text{C})$	
	JPt100	-200.0 to +550.0°C		

*1: PR40-20 : No reference junction compensation (0°C fix)

: Option (/N3: Expansion Inputs)

Recording and Printing

Recording Method

Pen model : Disposable felt pens, Plotter pen

Dot model : 6 color wire dot.

Pen Offset Compensation : ON/OFF selectable (Pen model only)

Effective Recording Width : 100mm(EW100), 180mm(EW180)

Chart : Plain-paper Z-fold chart (16m:EW100 20m:EW180)

Recording Period : Pen model: Continuous for each channel

Dot model: Max. 6ch/10sec, 12ch/15sec,

18ch/20sec, 24ch/30sec

Chart Speed Accuracy

Within $\pm 0.1\%$ (for recordings longer than 1000mm,

related to the grid of the chart paper)

Chart Speed

Pen model : 5 to 12000mm/h (82 increments)

Dot model : 1 to 1500mm/h (1mm step)

Chart Speed Change

speed 1, speed 2 change by remote control signals (option)

Recording Colors

Pen model : pen1=red, pen2=green, pen3=blue, pen4=violet
plotter pen=purple

Dot model : ch1,7,13,19=purple, ch2,8,14,20=red

ch3,9,15,21=green, ch4,10,16,22=blue

ch5,11,17,23=brown, ch6,12,18,24=black

*Color can be assigned to any channel.

*ch7 to 24: only EW180

Pen model dead band: 0.2% of recording span

Dot printing model resolution: 0.1mm

Recording Format

Analog recording : Zone recording, Partial expanded recording

Digital printout : Channel number or TAG (Dot model only),

Alarm, Periodic printout or Report printout,

Message printout, Record start time,

Chart speed printout, List printout,

Manual printout, SET UP List printout

Display

Display method

VFD (101X16 dot matrix):EW100

VFD (181X16 dot matrix):EW180

Display types

Multiple displays

Digital, bar, flag, DI/DO display etc. can be displayed.

*15 display types can be selected from approx. 80 display types.

Status display

Recording in progress (RECORD), Shared alarm (ALARM), Channel

No. display of occurring alarm (1 to 4ch or 1 to 24),

*ch7 to 24: only EW180

Chart end display (CHART END) For the model with option

(FAIL/chart end detection and output),

Math (MATH)

Setting

Settings display by interactive mode. In setting, navigator method is used.

Display updated interval can be selected from AUTO/MAN.

Bar graph display

Resolution: 1%

Measurement value: left/right (%) reference or center zero reference

display.

* Each channel selectable.

Alarm: Alarm setting level display and flashing display of occurring alarm.

Display brightness setting

Display brightness level: 1 to 8

Alarm

Number of Levels

Up to 4 level for each channel.

Alarm type

High and low limits, differential high and low limits, high and low rate-of-

change limits and delay high and low Interval time of rate-of-change

alarms:

The measurement interval times 1 to 15

Relay Contact Outputs (Option)

2 to 6 points selectable : EW100

2 to 24 points selectable : EW180

Hysteresis

0.0 to 1.0% (0.1% step) of recording span

*only High, Low alarm, common for all channels

and all levels

Display

Set value is indicated as a point on the bar graph

*only for bar graph display

In case of an alarm : - For digital display : Alarm type indicator

- Shared alarm display

- Alarm occurring channel No. is displayed

- For bar graph display: Flashing point indicator

Power Supply

Rated Power Voltage: 100 to 240VAC

(automatically selected depending on the power supply voltage)

Usable power voltage ranges: 90 to 132, 180 to 264VAC

Rated Power Frequency: 50 / 60 Hz, automatically selected

Power Consumption (In balance)

●EW100	100VAC	240VAC	Max.
1 to 4 pen	12VA	17VA	40VA
6 dot	13VA	18VA	40VA
●EW180	100VAC	240VAC	Max.
1 to 4 pen	17VA	25VA	55VA
6 to 24 dot	17VA	23VA	55VA

Optional Specification

Alarm output relay (/A1, /A2, /A3, /A4, /A5)

Number of output : 2, 4, 6, 12*, 24* points *: only EW180
Relay contact rating : 250VDC/0.1A (resistance load), 250VAC (50/60Hz) /3A

RS-422A/485 communication interface (/C3)

Measurement value and setting parameter read/write

Conforms to RS-422A and RS-485 standard

FAIL/chart end detection and output (/F1)

In CPU error occurrence or the chart end, output relay is activated.

Relay contact rating : 250VDC/0.1A (resistance load), 250VAC (50/60Hz) /3A

Clamped input (/H2)

Non-glare door glass (/H3)

Non-glare door glass for front door

Computation function (/M1)

Number of computation channel

Pen model: 8 channels

Dot model: 12 channels (EW100) 24 channels (EW180)

Arithmetic operation, Square, Absolute, Common logarithm,

Exponential, Power, Relational operator, Logic

Statistical computation : Statistical type : MAX, MIN, AVE, SUM, MAX-MIN

* Computation channel can be recorded

Cu10, Cu25 RTD input (/N1)

* Pt100 and JP100 inputs can be used together.

3-wire isolated RTD (/N2)

A, B, b legs of RTD are isolated for dot model

Expansion input (/N3)

Following input types can be supported besides standard inputs.

TC : PR40-20, PLII, NiNiMo, W/WRe26, Type N (AWG14), Kp vs Au7Fe

RTD : Pt25, Pt50, Ni100 (SAMA), Ni100 (DIN), Ni120, J263*B, Cu53, Cu100

* Cu100 : -0.00425 at 0°C

Remote control (/R1)

Below actions can be assigned to up to 5 points

Recording start/stop, Chart speed change, Message printout start,

Manual printout start, Alarm ACK, Time set, Math start/stop, Math reset

General Specification

Ambient temperature and humidity

0 to 50°C [32 to 122°F], 20 to 80% RH (at 5 to 40°C [41 to 104°F])

Input Resistance

10MΩ or more (TC, 20mV, 60mV, 200mV range)

Approx. 1MΩ (2V range or more)

Dielectric Strength

Power supply to ground terminal: 1500V AC (50 / 60Hz), 1 min

Contact output terminal to ground: 1500V AC (50 / 60Hz), 1 min

Measuring input terminal to ground: 1000V AC (50 / 60Hz), 1 min
Between measuring input terminals: 1000V AC (50 / 60Hz), 1 min
(except for RTD, since b-terminal is common).

Between remote control terminal to ground: 500V DC, 1min.

Memory backup

Lithium battery to save settings parameters

Approx. 10 years (23±2°C, 55±10% RH)

Safety and EMC standards

CSA CSA22.2 No.61010-1 (NRTL/C*) installation category II, measurement category II pollution degree 2

* For marking that includes NRTL, a mark with "US" (USA) printed on the right side of the CSA mark, and "C" (Canada) printed on the left side appears on this instrument.

CE EMC directive:

EN61326 compliance (Emission: Class A,

Immunity: Annex A)

EN61000-3-2 compliant

EN61000-3-3 compliant

EN55011 compliant, Class A Group 1

Low voltage directive:

EN61010-1 compliant, installation category II

measurement category II, pollution degree 2

Settings protection function

: Password method

Internal light : White LED

Operation position : 0° Frontwards: Within 30° from horizontal

Weight(approx.)

●EW100

1pen : 2.1kg, 2pen : 2.2kg, 3pen : 2.3kg, 4pen : 2.4kg, 6dot : 2.5kg


●EW180

1pen : 7.5kg, 2pen : 7.5kg, 3pen : 7.6kg, 4 en : 7.6kg,





6dot : 8.4kg, 12dot : 8.6kg, 18dot : 8.8kg, 24dot : 9.0kg

Rear Terminal Arrangements

SBR-EW100



SBR-EW180



SBR-EW100

Model code	Option code	Description
SBR—	EW101	SBR-EW100 1 pen recorder
	EW102	SBR-EW100 2 pen recorder
	EW103	SBR-EW100 3 pen recorder
	EW104	SBR-EW100 4 pen recorder
	EW106	SBR-EW100 6 dot recorder
	Language —2	English, degF & DST
Option	/A1	Alarm output relay (2 contacts)*1
	/A2	Alarm output relay (4 contacts)*1
	/A3	Alarm output relay (6 contacts)*1*2
	/C3	RS-422A/485 Interface
	/F1	FAIL/Chart end detection and output*2
	/H2	Clamped input terminal*3
	/H3	Non-glare door glass
	/M1	Mathematical Computations
	/N1	Cu10, Cu25 RTD input
	/N2	3 legs Isolated RTD*3*4
	/N3	Expansion inputs*5
	/R1	Remote controls (5 contacts)

Two or more option specification codes can be specified except for the following cases.

*1: only one of /A1, /A2, /A3 can be selected

*2: /A3 and /F1 can not be specified together

*3: /H2 and /N2 can not be specified together

*4: /N2 can be specified only for dot model

*5: TC: PR40-20, PL II, NiNiMo, W/WRe26, Type N(AWG14), Kp vs Au7Fe
RTD: Pt25, Pt50, Ni100(SAMA), Ni100(DIN), Ni120, J263*B, Cu53, Cu100

SBR-EW180

Model code	Option code	Description
SBR—	EW181	SBR-EW180 1 pen recorder
	EW182	SBR-EW180 2 pen recorder
	EW183	SBR-EW180 3 pen recorder
	EW184	SBR-EW180 4 pen recorder
	EW186	SBR-EW180 6 dot recorder
	EW187	SBR-EW180 12 dot recorder
	EW188	SBR-EW180 18 dot recorder
	EW189	SBR-EW180 24 dot recorder
	Language —2	English, degF & DST
Option	/A1	Alarm output relay (2 contacts)*1
	/A2	Alarm output relay (4 contacts)*1
	/A3	Alarm output relay (6 contacts)*1
	/A4	Alarm output relay (12 contacts)*1 *2
	/A5	Alarm output relay (24 contacts)*1 *2 *6
	/C3	RS-422A/485 Interface
	/F1	FAIL/Chart end detection and output*2
	/H2	Clamped input terminal*3
	/H3	Non-glare door glass
	/M1	Mathematical Computations
	/N1	Cu10, Cu25 RTD input
	/N2	3 legs Isolated RTD*3 *4
	/N3	Expansion inputs*5
	/R1	Remote controls (5 contacts)

Two or more option specification codes can be specified except for the following cases.

*1: only one of /A1, /A2, /A3, /A4, /A5 can be selected

*2: /F1 and /A5 can not be specified together

(/F1 and /A4 can not be specified together for pen model)

*3: /H2 and /N2 can not be specified together

*4: /N2 can be specified only for dot model

*5: TC: PR40-20, PL II, NiNiMo, W/WRe26, Type N(AWG14), Kp vs Au7Fe
RTD: Pt25, Pt50, Ni100(SAMA), Ni100(DIN), Ni120, J263*B, Cu53, Cu100

*6: /A5 can be specified only for dot model

Standard Accessories

Name	1 pen	2 pen	3 pen	4 pen	6/12/18/24 dot
Z-fold chart	1 piece				
6 color ribbon cassette	—	—	—	—	1 piece
Disposable felt-pen cartridge	Red	1 piece	1 piece	1 piece	1 piece
	Green	—	1 piece	1 piece	1 piece
	Blue	—	—	1 piece	1 piece
	Violet	—	—	—	1 piece
Plotter pen	Purple	1 piece	1 piece	1 piece	1 piece
Mounting brackets	2 piece				



Plotter pen



Disposable felt-pen cartridge

Separates/Optional Accessories

Name	Model code	Sales Unit	Specification	
Z-fold chart for EW100	B-100EX	1	10 pieces/unit	
Z-fold chart for EW180	R-100EX	1	10 pieces/unit	
6 color ribbon cassette for EW100	B9901AX	1	1 pieces/unit	
6 color ribbon cassette for EW180	B9906JA	1	1 pieces/unit	
Disposable felt-pen cartridge	Red	B9902AM	1	3 pieces/unit
	Green	B9902AN	1	3 pieces/unit
	Blue	B9902AP	1	3 pieces/unit
	Violet	B9902AQ	1	3 pieces/unit
Plotter pen	Purple	B9902AR	1	3 pieces/unit
Mounting brackets		B9900BX	2	
Shunt resistor (for screw input terminal)		415920	1	250Ω±0.1%
		415921	1	100Ω±0.1%
		415922	1	10Ω±0.1%
		438920	1	250Ω±0.1%
Shunt resistor (for clamped input terminal)		438921	1	100Ω±0.1%
		438922	1	10Ω±0.1%



•Before operating this product, read the instruction manual carefully to avoid incorrect operation.
•This product is intended for use with industrial machines, test and measuring equipment. It is not designed for use with medical equipment.
•If it is possible that an accident may occur as a result of the failure of the product or some other abnormality, an appropriate independent protection device must be installed.

Caution for imitated products

As products imitating our product now appear on the market, be careful that you don't purchase these imitated products. We will not warrant such products nor bear the responsibility for any damage and/or accident caused by their use.

RKC **RKC INSTRUMENT INC.**
(RIKA KOGYO CO.,LTD)

HEAD OFFICE : 16-6, KUGAHARA 5 CHOME OHTA-KU TOKYO 146-8515 JAPAN
PHONE : 03-3751-9799 (+81 3 3751 9799)
Email : info@rkcininst.co.jp
FAX : 03-3751-8585 (+81 3 3751 8585)
http://www.rkcininst.com/

萬和儀器有限公司

ONEHO INSTRUMENT LTD.

Address: 台中市西屯區朝富路213號23樓-2(A5)
TEL: +886 4 2238896
FAX: +886 4 2238891

WEB

