

Fluke 15Bplus Digital Multimeter



主要功能

- 600 V Cat III safety rating
- AC/DC voltage measurement up to 1000V
- AC/DC current measurement up to 10A
- Measures voltage, resistance, continuity, capacitance
- Diode test, data hold
- Large easy-to-read display with bright white backlight

產品概述: Fluke 15Bplus Digital Multimeter

Fluke quality is always within your reach

Unlock professional-grade precision, durability, and safety with the Fluke 15B+ Digital Multimeter. The Fluke 15B+ packs all the core functionality you need in a digital multimeter into a portable, rugged form tool that's easy-to-use with one hand, even with gloves on. From AC/DC voltage and current measurements up to 1000V and 10A, to comprehensive capabilities including resistance, and capacitance checks, the 15B+ is your go-to for troubleshooting a wide array of electrical issues.

The CAT III 600V safety rating provides peace of mind for everything from routine checks on electrical equipment and appliances, to checking voltage levels at power outlets or switches, to diagnosing issues with circuits. Ideal for both DIY enthusiasts and early career electricians looking to streamline their toolkit, the Fluke 15B+ is a reliable and versatile addition to your toolkit.

規格: Fluke 15Bplus Digital Multimeter

Accuracy Specifications

Accuracy is specified for 1 year after calibration, at operating temperatures of 18 °C to 28 °C, relative humidity at 0% to 75%. Accuracy specifications take the form of: $\pm$ (% of Reading + Number of Least Significant Digits).

Function	Range	Resolution	Accuracy
AC volts (40 Hz to 500Hz) ¹	4.000 V 40.00 V 400.0 V 1000 V	0.001 V 0.01 V 0.1 V 1 V	1.0% + 3
DC volts	4.000 V 40.00 V 400.0 V 1000 V	0.001 V 0.01 V 0.1 V 1 V	0.5% + 3
AC millivolts	400.0 mV	0.1 mV	3.0% + 3
DC millivolts	400.0 mV	0.1 mV	1.0% + 10
Diode test ²	2.000 V	0.001 V	10%
Resistance (Ohms)	400.0 Ω 4.000 k Ω 40.00 k Ω 400.0 k Ω 4.000 M Ω 40.00 M Ω	0.1 Ω 0.001 k Ω 0.01 k Ω 0.1 k Ω 0.001 M Ω 0.01 M Ω	0.5% + 3 0.5% + 2 0.5% + 2 0.5% + 2 0.5% + 2 1.5% + 3
Capacitance ³	40.00 nF 400.0 nF 4.000 μ F 40.00 μ F 400.0 μ F 1000 μ F	0.01 nF 0.1 nF 0.001 μ F 0.01 μ F 0.1 μ F 1 μ F	2% + 5 2% + 5 5% + 5 5% + 5 5% + 5 5% + 5
AC current μ A (40 Hz to 400 Hz)	400.0 μ A 4000 μ A	0.1 μ A 1 μ A	1.5% + 3
AC current mA (40 Hz to 400 Hz)	40.00 mA 400.0 mA	0.01 mA 0.1 mA	1.5% + 3
AC current A (40 Hz to 400 Hz)	4.000 A 10.00 A	0.001 A 0.01 A	1.5% + 3
DC current μ A	400.0 μ A 4000 μ A	0.1 μ A 1 μ A	1.5% + 3
DC current mA	40.00 mA 400.0 mA	0.01 mA 0.1 mA	1.5% + 3
DC current A	4.000 A 10.00 A	0.001 A 0.01 A	1.5% + 3
Backlight	Yes		

¹AC volts are specified from 1% to 100% of range. Inputs below 1% of range are not specified.

²Typically, open circuit test voltage is 2.0 V and short circuit current is <0.6 mA.

³Specifications do not include errors due to test lead capacitance and capacitance floor (may be up to 1.5 nF in the 40 nF range).

Function	Overload protection	Input impedance (Nominal)	Common mode rejection ratio	Normal mode rejection ratio
AC volts	1000 V ¹	>10 MΩ <100 pF	>60 dB at dc, 50 Hz or 60 Hz	-
AC millivolts	400 mV	>1MΩ, <100 pF	>80 dB at 50 Hz or 60 Hz	-
DC volts	1000 V ¹	>10 MΩ <100 pF	>100 dB at dc, 50 Hz or 60 Hz	>60 dB at 50 Hz or 60 Hz
DC millivolts	400 mV	>1MΩ, <100 pF	>80 dB at 50 Hz or 60 Hz	-

¹ 10⁶ V Hz Max

General specifications

Maximum voltage between any terminal and earth ground	1000 V
Display (LCD)	4000 counts, updates 3/sec
Battery type	2 AA, NEDA 15A, IEC LR6
Battery life	500 hours minimum
Temperature	
Operating	0 °C to 40 °C
Storage	-30 °C to 60 °C
Relative humidity	
Operating humidity	Non-condensing (<10°C) ≤90% RH at 10 °C to 30 °C; ≤75% RH at 30 °C to 40 °C
	40 MΩ range ≤80% RH at 10 °C to 30 °C; ≤70% RH at 30 °C to 40 °C
Altitude	
Operating	2000 m
Storage	12,000 m
Temperature coefficient	0.1 X (specified accuracy) /°C (<18 °C or >28 °C)
Fuse protection for current inputs	440 mA, 1000 V Fast Fuse, Fluke specified part only. 11A, 1000V Fast Fuse, Fluke specified part only.
Size (H x W x L)	183 x 91 x 49.5 mm
Weight	455 g
IP rating	IP 40
Safety	IEC 61010-1, IEC61010-2-030 CAT III 600 V, Pollution Degree 2
Electromagnetic Compatibility	IEC 61326-1: Portable EMC Environment

Class A equipment (industrial broadcasting & communication equipment)¹

¹ This product meets requirements for industrial (Class A) electromagnetic wave equipment and seller or user should take notice of it. This equipment is intended for use in business environments and is not to be used in homes.

機型



Fluke 15B+

Fluke 15B+ 數位萬用表

- TL75 測試導線，帶兩個帽
- 2 節 AA 電池
- 使用手冊



萬和儀器有限公司
ONEHO INSTRUMENT LTD.

台中

Address: 台中市北區崇德路一段631號7樓之2 B室
TEL: +886 4 22388896
FAX: +886 4 22388911

高雄

Address: 高雄市楠梓區大學二十街12號10樓
TEL: +886 7 3650837
FAX: +886 7 3651613

WEB



Fluke. 保持您的世界運作不懈。

Fluke Corporation
PO Box 9090, Everett, WA 98206 U.S.A.

更多資訊
U.S.A. (800) 443-5853
Europe/M-East/Africa
+31 (0)40 267 5100
Canada (800)-36-FLUKE
其他 +1 (425) 446-5500
www.fluke.com/zh-tw

©2024 Fluke Corporation. Specifications subject to
change without notice.
09/2024

Modification of this document is not permitted
without written permission from Fluke Corporation.