

Fluke 59 MAX/59 MAX+ Infrared Thermometer

Fits your budget. Fits your job.

With 65 years of expertise as the leader in the test tools industry, Fluke has built the 59 MAX and 59 MAX+ IR thermometers with the precision you need to do your job accurately and within your budget. Designed to withstand a 1 meter drop, you can count on these lightweight, compact IR thermometers to work when you need them.



Technical Data

Product highlights

- Precise laser technology for more accurate and repeatable measurements
- Large, easy-to-read backlit LCD display for easy viewing
- Small and lightweight design fits easily into your tool box
- IP40 rated for extra protection
- 10:1 Distance to Spot ratio, 59 MAX+ (8:1 Distance to Spot ratio, 59 MAX)
- Displays the minimum, maximum or average temperature, or the difference between two measurements
- Hi and Lo alarms for rapid display of measurements outside the limits
- Powered by one (1) AA battery
- One year warranty

Specifications

	59 MAX	59 MAX+
Temperature range	-30 °C to 350 °C (-22 °F to 662 °F)	-30 °C to 500 °C (-22 °F to 932 °F)
Accuracy (Calibration geometry with ambient temperature 23 °C ±2 °C)	$\geq 0^\circ\text{C}$: $\pm 2.0^\circ\text{C}$ or $\pm 2.0\%$ of reading, whichever is greater $\geq -10^\circ\text{C}$ to $<0^\circ\text{C}$: $\pm 2.0^\circ\text{C}$ $< -10^\circ\text{C}$: $\pm 3.0^\circ\text{C}$ $\geq 32^\circ\text{F}$: $\pm 4.0^\circ\text{F}$ or $\pm 2.0\%$ of reading, whichever is greater $\geq 14^\circ\text{F}$ to $<32^\circ\text{F}$: $\pm 4.0^\circ\text{F}$ $< 14^\circ\text{F}$: $\pm 6.0^\circ\text{F}$	$\geq 0^\circ\text{C}$: $\pm 1.5^\circ\text{C}$ or $\pm 1.5\%$ of reading, whichever is greater $\geq -10^\circ\text{C}$ to $<0^\circ\text{C}$: $\pm 2.0^\circ\text{C}$ $< -10^\circ\text{C}$: $\pm 3.0^\circ\text{C}$ $\geq 32^\circ\text{F}$: $\pm 3.0^\circ\text{F}$ or $\pm 1.5\%$ of reading, whichever is greater $\geq 14^\circ\text{F}$ to $<32^\circ\text{F}$: $\pm 4.0^\circ\text{F}$ $< 14^\circ\text{F}$: $\pm 6.0^\circ\text{F}$
Response time (95 %)	<500 ms (95 % of reading)	< 500 ms (95 % of reading)
Spectral response	8 μm to 14 μm	
Emissivity	0.10 to 1.00	
Distance to spot ratio	8:1 (calculated at 90 % energy)	10:1 (calculated at 90 % energy)
Display resolution	0.1 °C (0.2 °F)	
Repeatability (% of reading)	$\pm 1.0\%$ of reading or $\pm 1.0^\circ\text{C}$ ($\pm 2.0^\circ\text{F}$), whichever is greater	$\pm 0.8\%$ of reading or $\pm 1.0^\circ\text{C}$ ($\pm 2.0^\circ\text{F}$), whichever is greater
General specifications		
Power	1 AA IEC LR06 Battery	
Batter life	12 hours with laser and backlight on	
Weight	220 g (7.76 oz)	
Size	(156 x 80 x 50) mm (6.14 x 3.15 x 2) inches	
Operating temperature	0 °C to 50 °C (32 °F to 122 °F)	
Storage temperature	-20 °C to +60 °C (-4 °F to 140 °F), (without battery)	
Operating humidity	10 % to 90 % RH non-condensing @ 30 °C (86 °F)	
Operating altitude	2000 meters above mean sea level	
Storage altitude	12,000 meters above mean sea level	
Drop test	1 m	
Safety specifications		
Ingress protection rating	IP40 per IEC 60529	
Vibration and shock	IEC 68-2-6 2.5 g, 10 to 200 Hz, IEC 68-2-27, 50 g, 11 ms	
Compliance	EN/IEC 61010-1	
Laser safety	FDA and EN 60825-1 Class II	
Electromagnetic compatibility	61326-1 EN 61326-2	



萬和儀器有限公司
ONEHO INSTRUMENT LTD.

台中

Address: 台中市北區崇德路一段631號7樓之2 B室
TEL: +886 4 22388896
FAX: +886 4 22388911

高雄

Address: 高雄市楠梓區大學二十街12號10樓
TEL: +886 7 3650837
FAX: +886 7 3651613

WEB



Ordering information

Fluke 59 MAX Infrared Thermometer
Fluke 59 MAX+ Infrared Thermometer

Included:

Thermometer, One (1) AA battery,
registration card and user instructions.

Fluke. *The Most Trusted Tools
in the World.*

Fluke Corporation
PO Box 9090, Everett, WA 98206 U.S.A.

Fluke Europe B.V.
PO Box 1186, 5602 BD
Eindhoven, The Netherlands

For more information call:

In the U.S.A. (800) 443-5853 or
Fax (425) 446-5116
In Europe/M-East/Africa +31 (0) 40 2675 200 or
Fax +31 (0) 40 2675 222
In Canada (800)-36-FLUKE or
Fax (905) 890-6866
From other countries +1 (425) 446-5500 or
Fax +1 (425) 446-5116
Web access: <http://www.fluke.com>

©2013 Fluke Corporation.
Specifications subject to change without notice.
Printed in U.S.A. 6/2013 6000025A_EN

Modification of this document is not permitted
without written permission from Fluke Corporation.